



Tolerance: +/- 3% Specifications and product presentations are subject to change without prior notice.

### Normative references

FDA - Code of Federal Regulations (CFR) title 21, parts 175.300,177.1210 and 178.2010

## AIRE PESADO ATÓXICO

Code: AL07

Line Color: Crystal with white spiral

### Oharacteristics

Lightweight and flexible hose made from plasticized PVC and reinforced with rigid, shock-resistant PVC, making it very flexible. It is resistant to atmospheric agents and many chemicals. It does not transmit odor or taste.

# Application

• Light suction in processes where a non-toxic grade is required

Used for:

- Food
- Juices
- Medications

#### **Technical Information**

Internal surface smooth and external surface corrugated: extremely flexible.

Bending radius

4 times its interior diameter.

**Working temperature:** from 5°F to 122°F

Vacuum pressure

0.7 to 0.8 ATM = 21 to 24 in Hg.

Product Code	Commercial Size	Interior Diameter	Working pressure kg/cm² lb/ft²		Length	
Troduct Code	in	mm	(BAR)	(PSI)	m	ft
AL07CEB001203000	1/2	12.7	7	101	15 / 30	50 / 100
AL07CEB005803000	5/8	15.9	7	101	15 / 30	50 / 100
AL07CEB003403000	3/4	19.1	6	86	15/30	50 / 100
AL07CEB007803000	7/8	22.2	6	86	15/30	50 / 100
AL07CEB010003000		25.4	76	86	15/30	50 / 100
AL07CEB011403000	11/4	31.8	5//	72	15 / 30	50 / 100
AL07CEB011203000	11/2	\ \38.1\ \	\ \ \ 5 \ \ \	\ 72 \ \	15/30	50 / 100
AL07CEB013403000	13/4	\ 44.5		72	15/30	50 / 100
AL07CEB020003000	\\\2\\\	\ \ 50.8\ \	\ \ 4 \ \ \	58	15 / 30	50 / 100
AL07CEB021203000	\ \ \ 21/2\ \ \	63.5	4	58	/15///30   /	50 / 100
AL07CEB030003000	\ \\\3 \	76.2	4     )	50//	15/30	50 / 100
AL07CEB031203000	3 1/2	88.9	11/4/1/	150	15 / 30	50 / 100
AL07CEB040003000	-     4	/ /101.6//	1/4/	50	15 / 30	50 / 100
AL07CEB050002000	5//	127.0	3	36	10 / 20	30 / 60
AL07CEB060002000	116	152.4	3	36	10 / 20	30 / 60
AL07CEB080001000	8	203.2	2	29	10	30