



COMBUSTIBLE

Code: AL19
Line Color: Crystal blue with white spiral

Tolerance: +/- 3%
Specifications and product presentations are subject to change without prior notice.

Characteristics

Resistant and flexible hose made of plastified PVC with a rigid anti-shock spiral reinforcement, providing the flexibility of a hose and the durability of a rigid hose.

Resistant to a wide range of chemicals and atmospheric agents. Ideal for handling oils and gasoline.

Smooth internal and external surface (1" to 3"): facilitates clamp adjustment.

Smooth internal surface and corrugated external surface (4" to 6"): enhances flexibility.

Application

- Transfer and discharge of fuels
- Transfer and discharge of mineral and vegetable oils

Technical Information

Smooth internal and external surface
Smooth inner and corrugated outer surface

Working temperature:
from 5°F to 140°F

Bending radius
7 times its interior diameter.

Product Code	Commercial	Interior	Working pressure		Vacuum	Length	
	Size	Diameter	kg/cm ²	lb/ft ²	pressure	m	ft
	in	mm	(BAR)	(PSI)	in Hg		
AL19CZB010003000	1	25.4	9	131	30	15 / 30	50 / 100
AL19CZB011403000	1 1/4	31.8	9	131	30	15 / 30	50 / 100
AL19CZB011203000	1 1/2	38.1	9	131	30	15 / 30	50 / 100
AL19CZB020003000	2	50.8	8	116	30	15 / 30	50 / 100
AL19CZB021203000	2 1/2	63.5	7	102	30	15 / 30	50 / 100
AL19CZB030003000	3	76.2	6	87	30	15 / 30	50 / 100
AL19CZB040003000	4	101.6	5	73	30	15 / 30	50 / 100
AL19CZB050002000	5	127.0	4	58	28	10 / 20	30 / 60
AL19CZB060002000	6	152.4	3.5	51	28	10 / 20	30 / 60