



ENOFLEX

Code: AL28
Line Color: Crystal with red spiral

Tolerance: +/- 3%

Specifications and product presentations are subject to change without prior notice.

Normative references

FDA - Code of Federal Regulations (CFR) title 21, parts 175.300,177.1210 and 178.2010

Characteristics

Free of phthalates

Robust, non-toxic hose made of plasticized PVC with a rigid shock-resistant spiral reinforcement, combining the flexibility of a hose with the strength of a rigid pipe. Resistant to atmospheric agents and a wide range of chemicals.

Internal and external surface smooth (1/2" to 3" and 10"): facilitates clamp adjustment.

Internal surface smooth and external surface corrugated (3 1/2" to 8"): enhances flexibility.

Application

- Transfer of wines
- Transfer of dairy products, vegetable oils, and mineral oils

Technical Information

Smooth internal and external surface
Smooth inner and corrugated outer surface

Bending radius
5 times its interior diameter.

Working temperature:
from 14°F to 149°F

Vacuum pressure
0.8 ATM = 24 in Hg

Product Code	Commercial Size in	Interior Diameter mm	Working pressure		Length	
			kg/cm ² (BAR)	lb/ft ² (PSI)	m	ft
AL28CER001203000	1/2	12.7	9	130	15 / 30	50 / 100
AL28CER005803000	5/8	15.9	9	130	30	100
AL28CER003403000	3/4	19.1	7	101	30	100
AL28CER007803000	7/8	22.2	7	101	30	100
AL28CER010003000	1	25.4	7	101	30	100
AL28CER011403000	1 1/4	31.8	6	86	30	100
AL28CER011203000	1 1/2	38.1	6	86	30	100
AL28CER020003000	2	50.8	5	72	30	100
AL28CER021203000	2 1/2	63.5	5	72	30	100
AL28CER030003000	3	76.2	5	65	30	100
AL28CER031203000	3 1/2	88.9	5	65	30	100
AL28CER040003000	4	101.6	5	65	30	100
AL28CER050002000	5	127.0	4	50	10 / 20	30 / 60
AL28CER060002000	6	152.4	3	43	10 / 20	30 / 60
AL28CER080001000	8	203.2	3	36	10	30
AL28CER100000610	10	254.0	2	35	6.1	20