



ESTRUCTURAL

Code: AL29
Line Color: Black

Tolerance: +/- 3%
Specifications and product presentations are subject to change without prior notice.

Characteristics

Lightweight corrugated hose made of high-density polyethylene. Adapts to uneven terrain. Chemically resistant to alkaline materials and acids, as well as organic and inorganic solvents.

Application

- Cable (strand) protection in construction (post-tensioned)
- Low-pressure water movement
- Electrical wiring in cities and highways
- Can be used outdoors or buried

Technical Information

corrugated inner and outer surface

Working temperature:
from 14°F to 140°F

Bending radius
7 times its interior diameter.

Product Code	Commercial Size	Interior Diameter	Exterior Diameter	Length	
	in	mm	mm	m	ft
AL29NEG007803000	7/8	22.0	26.0	15 / 30	50 / 100
AL29NEG010003000	1	23.0	28.0	15 / 30	50 / 100
AL29NEG011403000	1 1/4	32.0	38.0	15 / 30	50 / 100
AL29NEG011203000	1 1/2	37.0	41.0	15 / 30	50 / 100
AL29NEG015803000	1 5/8	42.0	50.0	15 / 30	50 / 100
AL29NEG013403000	1 3/4	45.0	54.0	15 / 30	50 / 100
AL29NEG020003000	2	49.0	57.0	15 / 30	50 / 100
AL29NEG021203000	2 1/2	65.0	75.0	15 / 30	50 / 100
AL29NEG030003000	3	80.0	89.0	15 / 30	50 / 100
AL29NEG040003000	4	99.0	110.0	15 / 30	50 / 100
AL29NEG060002000	6	140.0	155.0	10 / 20	20 / 50
AL29NEG080002000	8	180.0	200.0	10 / 20	20 / 50
AL29NEG100001000	10	228.0	250.0	10	25