

Specifications and product presentations are subject to change without prior notice.

Application

- · Where static charge elimination is required.
- Transfer of powder, pellets, granular materials, and vacuum lines in paper mills.
- Transport of food, juices, jams, syrups, wines, dairy products, and soft drinks.
- Transport of beverages with an alcohol concentration not exceeding 28% (56° G.L.).
- Transport of dry granular materials.

alaflex Simply Flexible High technology in flexible hoses

HEAVY DUTY CRISTAL CON ANTIESTÁTICO ATÓXICO

Code: AL33

Line Color: Crystal with crystal blue spiral

Oharacteristics

Robust hose, non-toxic, made of plasticized PVC with a rigid PVC spiral reinforcement, combining the flexibility of a hose with the strength of a rigid pipe. Resistant to atmospheric agents and a wide range of chemicals. Made with copper wire for static charge elimination.

Normative references

FDA - Code of Federal Regulations (CFR) title 21, parts 175.300,177.1210 and 178.2010

Technical Information

Smooth inner and corrugated outer surface

Working temperature: from 14°F to 140°F

Bending radius

6 times its interior diameter.

Vacuum pressure 0.8 ATM = 24 in Hg

Product Code	Commercial Size in	Interior Diameter mm	Working pro kg/cm² (BAR)	essure lb/ft² (PSI)	Len m	gth ft
AL33CEC011403000	11/4	31.8	3	44	15 / 30	50 / 100
AL33CEC011203000	11/2	38.1	3	\44\\	15 / 30	50 / 100
AL33CEC020003000	2	51,3	\\\\\3\\\\	\44\\\	15 / 30	50 / 100
AL33CEC021203000	21/2	\\\63.5\\\	\\\\2\\\\	29	15 / 30	50 / 100
AL33CEC030003000	3 \ \ \ \	77.0	2	29//	15 / 30	50 / 100
AL33CEC040003000	4	101.6	1111/2/1/	29	15 / 30	50 / 100
AL33CEC050002000	5	1/127.0//	2	29	10 / 20	30 / 60
AL33CEC060002000	6	152.4	2	29	10 / 20	30 / 60