



Tolerance: +/- 3% Specifications and product presentations are subject to change without prior notice.

Normative references

External diameters from 1/2" to 3" comply with IAPMO PS 33 - 2010c / NSF 50 standards.

HIDROTEC

Code: AL34 Line Color: White

O Characteristics

Durable hose, made with flexible PVC and rigid shock-resistant PVC reinforcement; providing the flexibility of a hose and the solidity of a rigid pipe. Resistant to atmospheric agents and chemicals.

Smooth internal and external surface (1/2" and 4"): facilitates clamp adjustment.

o Application

• Ideal for replacing traditional pipes in installations for hot tubs, swimming pools, drainage lines, and peripheral hydraulic systems.

Technical Information

Smooth internal and external surface

Working temperature: from 5°F to 149°F

Product Code	Commercial Interior Diar Size mm		nm	Working pressure kg/cm ² lb/ft ²		MBR	Length	
	in	min	max	(BAR)	(PSI)	in	m	π
AL34BLA001203000	1/2	21.3	21.8	~7	101	2.0	15 / 30	50 / 100
AL34BLA003403000	3/4	26.6	27.1	UN XIII	101	2.0	15 / 30	50 / 100
AL34BLA010003000	ADP	33.3	33.9	////\//////////////////////////////////	101	3.0	15 / 30	50 / 100
AL34BLA011403000	11/4	42,1	42.6	6	86	3.0	15 / 30	50 / 100
AL34BLA011203000	11/2	48.2	48.7	5	72 P	5.0	15 / 30	50 / 100
AL34BLA020003000	2	60.2	60.8	500	PA2	8.0	15 / 30	50 / 100
AL34BLA021203000	21/2	69.9	70.5	PL5	72	8.0	15 / 30	50 / 100
AL34BLA030003000	3	88.8	89.4	5	72	8.0	15 / 30	50 / 100
AL34BLA040003000	A PP	114.3	114.9	5	72	8.0	15 / 30	50 / 100