



Tolerance: +/- 3%
Specifications and product presentations are subject to change without prior notice.

MINAS

Code: AL37
Line Color: Crystal with gray spiral

Characteristics

Light and flexible hose made of high molecular weight plasticized PVC with a rigid shock-resistant PVC spiral reinforcement, making it very flexible.

Resistant to atmospheric agents and a wide range of chemicals.

Application

- For medium suction and/or transfer.
- For waste processing pumps, construction, and mining.
- Handling slurries, gold dredging, and irrigation lines.

Technical Information

Internal surface smooth and external surface corrugated: extremely flexible.

Bending radius
5 times its interior diameter.

Working temperature:
from -4°F to 150.8°F

Vacuum pressure
1 ATM = 30 in Hg

Product Code	Commercial Size in	Interior Diameter mm	Working pressure		Length	
			kg/cm ² (BAR)	lb/ft ² (PSI)	m	ft
AL37CEG010003000	1	25.4	6	86	15 / 30	50 / 100
AL37CEG011403000	1 1/4	31.8	5	72	15 / 30	50 / 100
AL37CEG011203000	1 1/2	38.1	5	72	15 / 30	50 / 100
AL37CEG020003000	2	50.8	4	58	15 / 30	50 / 100
AL37CEG021203000	2 1/2	63.5	4	58	15 / 30	50 / 100
AL37CEG030003000	3	76.2	4	50	15 / 30	50 / 100
AL37CEG040003000	4	101.6	4	50	15 / 30	50 / 100
AL37CEG050002000	5	127.0	3	36	10 / 20	30 / 60
AL37CEG060002000	6	152.4	3	36	10 / 20	30 / 60
AL37CEG080001000	8	203.2	2	29	10	30