

TRANSMETAL PARA COMBUSTIBLES

Code: AL47 Line Color: Crystal black

O Characteristics

Light and flexible hose made of plasticized PVC with steel reinforcement, offering the flexibility of a hose and the strength of a rigid pipe. Smooth internal surface.

Good resistance to suction and pressure.

Resistant to atmospheric agents and many chemicals.

Ideal for handling oils and gasoline.

o Application

• For use in the transfer of fuels and oils

Technical Information

Smooth inner and outer surface

Bending radius

7 times its interior diameter.

Working temperature: from 5°F to 149°F

Vacuum pressure 0.8 ATM = 24 in Hg

| Product Code | Commercial Size in | Interior Diameter mm | Working pr kg/cm² (BAR) | essure lb/ft² (PSI) | Len m | gth ft |
|------------------|--------------------------|----------------------------|-------------------------------|---------------------------|----------|-----------|
| AL47CNE003403000 | 3/4 | 19.1 | 8 | 115 | 15 / 30 | 50 / 100 |
| AL47CNE010003000 | | 25.4 | 8 | 115 | 15 / 30 | 50 / 100 |
| AL47CNE011403000 | 11/4 | 31.8 | /////★///// | 101 | 15 / 30 | 50 / 100 |
| AL47CNE011203000 | (11/2) | 38.1 | \\\\\7\\\) | 101 | 15 / 30 | 50 / 100 |
| AL47CNE020003000 | 2 | 50.8 | 6/// | 86 | 15 / 30 | 50 / 100 |
| AL47CNE021203000 | 21/2 | 63.5 | JPP6PE | 86 | 15 / 30 | 50 / 100 |
| AL47CNE030003000 | 3 | 176.2 | 6 | 86 | 15 / 30 | 50 / 100 |
| AL47CNE040003000 | APP | 101.6 | 6 | 86 | 15 / 30 | 50 / 100 |



